

KITCHEN TYPE FIRE EXTINGUISHERS

CLEAN AGENT TYPE FIRE EXTINGUISHER.

Safe to use on all your sensitive quipment, the clean Agent Extinguisher brings you the added benefit of being the world's most advanced, and by far the most eco-friendly extinguisher. Clean Agent Extinguishers leave no residue, pack in mega power and are absolutely safe for use on any sensitive electronic equipment.



MODEL	SPF-2CA	SPF-4CA	SPF-6CA
CAPACITY	2 KG	4 KG	6 KG
FIRE RATING	1A-BB	2A-BB	3A-34B
OPERATING TEMPERATURE	-20°C TO +55°C	-20°C TO +55°C	-20°C TO +55°C
DISHAREGE TIME	MORE THAN 2 MTRS.	MORE THAN 2 MTRS.	MORE THAN 2 MTRS.
CHARGE PRESSURE	15 BAR	15 BAR	15 BAR
TEST PRESSURE	35 BAR	35 BAR	35 BAR
OPERATING VALVES	SQUEEZE GRIP TYPE	SQUEEZE GRIP TYPE	SQUEEZE GRIP TYPE
EXTINGLISHER MEDIA	CLEAN AGENT	CLEAN AGENT	CLEAN AGENT
EXPELLANT	NITROGEN	NITROGEN	NITROGEN

- 1 Year warranty
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Supplied with wall bracket
- Full range of spare parts are available

A

TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.

B

TYPE 'B' FOR USE ON PETROL, OIL PAINTS, SPIRIT, CHEMICALS ETC.

C

TYPE 'C' FOR USE ON COOKING & WELDING GAS, ELECTRICAL FIRE ETC.

SHORT BRANCH PIPE WITH NOZZLE

TECHNICAL SPECIFICATIONS

Size of Branch Pipe : 63 MM
Size of Nozzles : 6MM, 12MM, 15MM, 20MM and 25MM
Material : Gun metal / stainless / Aluminum Alloy
Conforming Specification : IS 903:1993

Performance Test:
Hydrostatic Test : Tested at 21 KGF / CM 2
Working Pressure : 7 KGF / CM2
Finish : Natural Polished
Hologram : Sticker Stuck on Nozzle



Type of Material	Stainless Steel	Gun Metal
Body, Assembly	Stainless Steel - IS:3444	LTB2 - IS:318
Rubber Washer	IS:937 (Type-B)	IS:397 (Type-B)

SWINGING TYPE WALLMOUNTED FIRTAID HOSEREELDRUM

TECHNICAL SPECIFICATIONS

Conforming to: IS:884/1958
Size: Inlet: 1" Threaded Inlet Connection
Type: Swinging 180° Wall Mounting
Outlet: 3/4"/1"/1-1/2 outlet connection for Hose to accommodate 30/36/40 Mtrs. Hose to.



PerformanceTest
Hydrostatic Test: Tested at 21KGF/CM2
Range & Water Flow rate test at 7 KGF/CM2
(A) Discharge: 24 LPM
(B) Range (JetLength): 6Mtr (Min)

Hologram : StickerStuckonWheel	
Hub Sides & Wall Bracket	M.S. Sheet of IS : 513
Swivel Joint	LTB - 2 of IS : 318
Pipe with Fitting	Steel of IS : 1239 Part 1
Nozzle	IS : 8090
Hose Reel Tubing	Thermoplastic Hose conforming to IS : 12585

ABOUT US

Agni tech engineers is a company with a proven track record in fire safety. We are group of well qualified and Experienced in the field of fire safety We have Earned the respect of our customer by rendering prompt & efficient services. Our long standing experience and individual client care always allows us to tune in with our customers demands continue to provide a personal, high quality service that can be relied upon.

OUR SERVICES

Installation, repair and refilling of fire extinguishers and fire hydrant system. Installation and repairs of heat detectors & fire alarm systems annul maintenance/request inspection.




AGNI TECH ENGINEERS

in the line of fire

L-207. Ashoka Mews Behind Sheetal Petrol Pump,
Kondhwa Khurd, Pune, Maharashtra - 411048
Email : agnitechb2b@gmail.com

Mob.: 9970801523 / 9832410230



"LEARN NOT TO BURN"

AGNI TECH ENGINEERS

in the line of fire

Manufacture, Supply, Design & Maintenance
of fire Fighting Equipments

FIRE EXTINGUISHERS | HYDRANTS | HOSE BOXES
FIRE HOSE REELS | SPRINKLERS | ACCESSORIES | SIGNAGES

ABC STORED PRESSURE POWDER

1KG, 2KG, 4KG,
6KG and 9KG

Powder fire extinguishers are ideal for use on class **A**, **B** and **C** Fire Risks. Agnitech fire Powder fire extinguishers are available in 1KG, 2KG,4KG, 6KG and 9KG standard versions



- ISI Marked
- 1 year warranty
- Safe for use on live electrical equipment
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Supplied with wall bracket
- Full range of spare parts are available



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.



TYPE 'B' FOR USE ON PETROL, OIL PAINTS, SPIRIT, CHEMICALS ETC.



TYPE 'C' FOR USE ON COOKING & WELDING GAS, ELECTRICAL FIRE ETC.

MODEL	SPF -1ABC	SPF -2ABC	SPF -4ABC	SPF -6ABC	SPF -9ABC
CYLINDER MATERIAL	M.S.	M.S.	M.S.	M.S.	M.S.
CAPACITY (KG)	1	2	2	6	9
FIRE RATING	1A 8B	1A 13B	2A 21B	3A 34B	4A 55B
EXTINGUISHING MEDIUM	POWDER	POWDER	POWDER	POWDER	POWDER
TEMPERATURE RANGE	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C
DISCHARGE TIME	MORE THAN 08. S	MORE THAN 08. S	MORE THAN 13. S	MORE THAN 13. S	MORE THAN 13. S
DISCHARGE RANGE	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M
TEST PRESSURE	35 BAR	35 BAR	35 BAR	35 BAR	35 BAR
EXPELLANT	NITROGEN	NITROGEN	NITROGEN	NITROGEN	NITROGEN

Co2 TYPE FIRE EXTINGUISHERS CARBON DIOXIDE

2KG, 3KG,
4.5KG

Carbon Dioxide fire extinguishers are ideal for use on Class **B** & **C** Fire Risks. Agni tech Fire carbon dioxide fire extinguishers are available in 2KG,3KG, and 4.g.KG standard

- ISI Marked
- 1 year warranty
- Safe for use on live electrical equipment
- Fully refillable
- Controlled discharge
- Controlled discharge
- Supplied with wall bracket
- Full range of spare parts are available



MODEL	SPF-2CO	SPF-3CO	SPF-4.5CO
CYLINDER MATERIAL	M.S.	M.S.	M.S.
CAPACITY (KG)	2	3	4.5
FIRE RATING	8B	13B	21B
EXTINGUISHING MEDIUM	Co2 Gas IS 15222	Co2 Gas IS 15222	Co2 Gas IS 15222
TEMPERATURE RANGE	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C
DISCHARGE TIME	MORE THAN 08. S	MORE THAN 08. S	MORE THAN 18. S
DISCHARGE RANGE	MORE THAN 01 M	MORE THAN 02 M	MORE THAN 02 M
TEST PRESSURE	250 BAR	250 BAR	250 BAR



TYPE 'B' FOR USE ON PETROL, OIL PAINTS, SPIRIT, CHEMICALS ETC.



TYPE 'C' FOR USE ON COOKING & WELDING GAS, ELECTRICAL FIRE ETC.

MECHANICAL FOAM TYPE FIRE EXTINGUISHERS FOAM 6 Ltr, 9 Ltr.

Foam fire extinguishers are ideal for use on class **A** and **B** fire Risks. Agni tech fire Foam fire extinguishers are available in 6ltr and 9ltr standards models.



- ISI Marked
- 1 year warranty
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Supplied with wall bracket
- Full range of spare parts are available



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.



TYPE 'B' FOR USE ON PETROL, OIL PAINTS, SPIRIT, CHEMICALS ETC.

MODEL	SPF-6MF	SPF-9MF	SPF-6MFCT	SPF-9MFCT
CYLINDER MATERIAL	M.S.	M.S.	M.S.	M.S.
CAPACITY (KG)	6	9	6	9
FIRE RATING	3A 34B	4A 55B	3A 34B	4A 55B
EXTINGUISHING MEDIUM	AFFF FOAM IS 4989	AFFF FOAM IS 4989	AFFF FOAM IS 4989	AFFF FOAM IS 4989
TEMPERATURE RANGE	+5°C to +55°C	+5°C to +55°C	+5°C to +55°C	+5°C to +55°C
DISCHARGE TIME	MORE THAN 13. S	MORE THAN 13. S	MORE THAN 13. S	MORE THAN 13. S
DISCHARGE RANGE	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M
TEST PRESSURE	35BAR	35BAR	35BAR	35BAR
EXPELLANT	NITROGEN	NITROGEN	Co2	Co2

WATER TYPE EXTINGUISHERS WATER 6 Ltr, 9 Ltr.

Water Fire Extinguishers are ideal for extinguishing Class **A**. Agni tech Water Fire Extinguishers are perfect for use in a range of applications including offices and warehouses and the extinguishing is just pure water making the fire extinguishers extremely. Environmentally friendly and quick and simple to discharge test. A high Performance water 6ltr & 9ltr version is also available.



MODEL	SPF-6W	SPF-9W	SPF-6WCT	SPF-9WCT
CYLINDER MATERIAL	M.S.	M.S.	M.S.	M.S.
CAPACITY (KG)	6	9	6	9
FIRE RATING	3A	4A	3A	4A
EXTINGUISHING MEDIUM	WATER	WATER	WATER	WATER
TEMPERATURE RANGE	+5°C to +55°C	+5°C to +55°C	+5°C to +55°C	+5°C to +55°C
DISCHARGE TIME	MORE THAN 13. S	MORE THAN 13. S	MORE THAN 13. S	MORE THAN 13. S
DISCHARGE RANGE	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M
TEST PRESSURE	35BAR	35BAR	35BAR	35BAR
EXPELLANT	NITROGEN	NITROGEN	Co2	Co2

- ISI Marked
- 1 year warranty
- Easy to read pressure gauge
- High quality corrosion resistant finish
- Supplied complete with wall mounting bracket
- Full range of spare parts are available



TYPE 'A' FOR USE ON PAPER, WOOD, CLOTH, PLASTICS ETC.

TROLLEY TYPE FIRE EXTINGUISHERS HIGHER CAPACITY FIRE EXTINGUISHERS 25KG, 50KG, 75KG

Agnitech fire extinguisher trolley units are available in BC/ABC Powder and AFFF Foam versions and offer exceptional value for money as well as the high quality that you would expect from Agni tech fire fighting products. Agnitech fire trolley units are ideal for use in a wide range of commercial and industrial.



CAPACITY	25/50/75KG	6.5/9/22.5KG	50 Liter	50 Liter
IS No.	IS 10658	IS 2878	IS 13386	IS 13385
Min. Jet Length (in mtrs)	6/8/10 Mtrs	6/8/10 Mtrs	20 Mtrs	10 Mtrs
Discharge Percentage	85 %	95 %	95 %	95 %
Discharge Time	25/40/50 S	30/36/60 S	60-180 S	60-180 S
Charge Pressure	14 KG/CM²	-	14 KG/CM²	14 KG/CM²
Cylinder	IS 10658	IS 2878	IS 13386	POWDER
Test Pressure	POWDER	POWDER	-20°C to +55°C	30 BAR
Extinguisher Media	Dry powder IS14609 / IS 4308	Co2 Gas Is: 15222	AFFF FOAM	WATER
Expellant	Co2	Co2	Co2	Co2

CLEAN AGENT FIRE EXTINGUISHERS WET CHEMICAL (K-CLASS)

2KG, 4KG,
6KG, fire
extinguishers

Stored Pressure, 2KG, 4KG, & 6KG fire extinguishers Wet chemical fire extinguishers will Class **K** fire risks and are designed for use against kitchen and fat fires. A unique feature of the Agni Tech fire wet chemical fire extinguishers is that the extinguishers can be operated from a distance of approximately 3-4 Meters away reducing danger to the fire extinguisher operator.

MODEL	SPF-2K	SPF-4K	SPF-6K	SPF-9K
CYLINDER MATERIAL	S.S	S.S	S.S	S.S
CAPACITY (KG)	2	4	6	9
EXTINGUISHING MEDIUM	WET CHEMICAL	WET CHEMICAL	WET CHEMICAL	WET CHEMICAL
DISCHARGE TIME	MORE THAN 08 S	MORE THAN 13 S	MORE THAN 13 S	MORE THAN 13 S
DISCHARGE RANGE	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M	MORE THAN 02 M
TEST PRESSURE	35BAR	35BAR	35BAR	35BAR
EXPELLANT	NITROGEN	NITROGEN	NITROGEN	NITROGEN



- ISI Marked
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Supplied with wall bracket
- Full range of spare parts are available



COOKING MEDIA COOKING OILS & FATS